


ADVANCED PROGRAMMABLE SWITCHBOX

STAR
Safety Technologies by *Grote*



SB44-8



PROGRAMMABLE SWITCHES

FEATURES & BENEFITS

- 8-button control panel for operating up to 8 lights/ devices
- Red backlit silicone rubber keypad with 14 programmable brightness settings
- Programmable switching options: Ground-side switching, Momentary switching, Normally Closed, Flashing Output with Phase settings, and Audio feedback
- Option to program as a stand-alone Traffic Director Controller for logic-controlled sticks
- Smartphone Programmable
- Durable polycarbonate housing
- Includes 12-pin wire harness to simplify installation
- Includes aluminum U-bracket (274-SB44-U) and stainless steel hardware for versatile mounting
- Includes replaceable velvet finish Lexan™ button labels
- Dimensions: 2 5/8" H x 4 1/8" W x 1/2" D
- Operating range: 9-16V DC
- Operating temperature range: -40°F to 131°F
- 6 outputs at 2.5A average (5 A peak)
- 2 outputs at 0.06A average



274-SB44-H
(SB44-5 not included)



274-SB44-U



274-SB44-VC



PART	DESCRIPTION
SB44-8	Programmable switchbox, 8 buttons, U-bracket included
274-SB44-H	Headliner Bracket
274-SB44-U	U-Bracket
274-SB44-ULP	Low profile U-Bracket
274-SB44-VC	Visor Clip Bracket

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF223 SB44-5, SB44-8 REV B 7-27-23



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*

5 BUTTON CONTROLLER SWITCHBOX

STAR
Safety Technologies by *Grote*



SB44-5



PROGRAMMABLE SWITCHES

FEATURES & BENEFITS

- 5-button standard Traffic Director control option and auxiliary switches
- Built-in LED display mimics Traffic Director output
- Red backlit silicone rubber keypad with 14 programmable brightness settings
- Option to program as a 4-output switchbox
- Durable polycarbonate housing
- Hardwired 11" pigtail
- Includes aluminum U-bracket (274-SB44-U) and stainless steel hardware for versatile mounting
- Includes replaceable velvet finish Lexan™ button labels
- Dimensions: 2 5/8" H x 4 1/8" W x 1/2" D
- Operating range: 9-16V DC
- Operating temperature range: -40°F to 131°F
- 2 outputs at 2.5A average (5 A peak)
- 2 outputs at 0.06A average

PART	DESCRIPTION
SB44-5	Programmable switchbox, 5 buttons, U-Bracket included
274-SB44-H	Headliner Bracket
274-SB44-U	U-Bracket
274-SB44-ULP	Low profile U-Bracket
274-SB44-VC	Visor Clip Bracket

 **Warning:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF223 SB44-5, SB44-8 REV B 7-27-23



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*