







REV	ECR	DESCRIPTION	DATE		
Α	17806	INITIAL DRAWING REQUEST	03/25/2021		

SPECIFICATIONS:

OPERATING RANGE: 9-16VDC NOMINAL VOLTAGE: 12 VDC

OUTPUT CURRENT: 12.8VDC 6@2.5A AVERAGE EACH, 2@0.05A

6 LED SIMULATED TRAFFIC DIRECTOR FEEDBACK

(LEFT, RIGHT, CENTER OUT, WARN)
CELL PHONE PROGRAMMABLE OPTIONS

OPERATING TEMPERATURE RANGE: -40F (-40C) TO 131F (55C)

CONNECTIONS:

12" LONG HARNESS WITH 12 PIN CONNECTOR

PIN#1: 22AWG BROWN (PB 8)
PIN#2: 22AWG GRAY (PB 1)
PIN#3: 22AWG BLACK (- GROUND)
PIN#4: 18AWG RED (+ POWER)
PIN#5: 18AWG RED (+ POWER)
PIN#6: 18AWG RED (+ POWER)
PIN#7: 22AWG PURPLE (PB 7)

PIN#7: 22AWG PURPLE (PB 7) PIN#8: 22AWG BLUE (PB 6) PIN#9: 22AWG GREEN (PB 5) PIN#10: 22AWG YELLOW (PB 4) PIN#11: 22AWG ORANGE (PB 3)

PIN#12: 22AWG WHITE (PB 2)

INSTALLATION:

UNIVERSAL BRACKET 274-SB44-U (INCLUDED) HEADLINER BRACKET 274-SB44-H (OPTIONAL) #8-32 HARDWARE (BRACKET TO CONTROLLER)

MATERIALS:

OUTER HOUSING: POLYCARBONATE

KEYPAD: SILICONE RUBBER
BRACKETS: ALUMINUM
HARDWARE: STAINLESS STEEL
BUTTON LABELS: VELVET FINISH LEXAN

PRODUCT LABEL:

WHITE POLYESTER STOCK 3.0" X .375"

COLOR STAR LOGO

INDIVIDUAL PACKAGING: APPROXIMATELY 142g(0.31 lb.)

INDIVIDUAL BROWN BOXES

MODEL INFORMATION PRINTED ON ON LABEL

INSTRUCTION SHEET:

1 PROVIDED (ENGLISH)

UNLESS OTHERWISE SPECIFIED	DRAWN BY:	MD	STAR H	IFADIICHT & LANTE	RN CO	INC	
DIMENSIONS ARE IN INCHES	DRAWING APPROVED BY ECR		STAR HEADLIGHT & LANTERN CO., INC. 455 Rochester St. Avon NY 14414 Ph:(585) 226-9500 Fax: (585) 226-2029				
TOLERANCES:	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF						
ANGULAR: ± 2 DEG.							
.X ± .100 .XX ± .020	ANY REPRODUC	T & LANTERN CO., INC TION IN PART OR AS A	MODEL:	SB44-8			
.XXX ± .005 .XXXX ± .001	WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC.		TITLE:	CD 4.4 O A 4 O DEL DD A WILLIO			
ROHS COMPLIANT: YES	IS STRICTLY PROHIBITED.		SB44-8 MODEL DRAV	DEL DRAWING			
MATERIAL:			DWG. NO.			REV	
N/A				SB44-8 A			
FINISH:							
N/A			SCALE: 1:2	DO NOT SCALE FROM DRAWING	SHEET	1 OF 1	