

STARFLASH™ FLASHER MODULES & HEADS

STARFLASH™



B. HH2501



C. HH2502



D. HH3930



E. HH3970



F. HH3971



G. FM3666



H. FM3669C



I. DRL366-1

Models & Specifications:

- A. HH2501 Mini-Rectangular halogen head, grille mount Halogen warning light.
Lens color: Amber, Blue, Clear, Red
- B. HH2502 Rectangular halogen head, grille mount halogen warning light.
Lens color: Amber, Blue, Clear, Red
- C. HH3930 Par-36 Round sealed beam head. Grille or rear mount halogen warning light with shock-resistant black rubber housing.
Lens color: Amber, Blue, Clear, Red
- D. HH3970 7" Diameter sealed beam head:
For ambulances, fire trucks, rescue vehicles, school buses.
Lens color: Amber, Blue, Clear, Red
- E. HH3971 7" Rectangular sealed beam head:
For ambulances, fire trucks, rescue vehicles
Lens color: Amber, Blue, Clear, Red
- F. FM3666: 12V DC Mechanical Flasher.
Flash Rate: 1.2 flashes per second per lamp.
- FM3662: 12V DC Solid state flasher for up to 100 Watts per side.
Flash Rate: 2.4 flashes per second per lamp.
- FM3662-24: 24V DC Solid state flasher for up to 100 Watts per side.
Flash Rate: 2.0 flashes per second per lamp.
- FM3667: 12V DC Solid state flasher for back-up/brake light.
Flash Rate: 2.4 flashes per second per lamp.
- FM3669: 12V DC Solid state flasher with DRL for up to 100 Watts per side.
DRL override, night time cut off.
Flash Rate: 1.9 flashes per second per lamp.
- G. FM3669C: 12V DC Solid state flasher for up to 100 Watts per side.
Customer selectable flash patterns (Alternating or Simultaneous).
Night time cut off. Compatible with factory installed DRL control.
Flash Rate: Alternating: 1.9 flashes per second per lamp.
Simultaneous: 3.6 flashes per second per lamp.
- FM6901: 12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 1.9 flashes per second per lamp.
- FM6902: 12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- FM6903: 12V DC Solid state flasher. Simultaneously flashes headlights. Has high beam override and night time cut off. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- FM6904: Flashes left headlight three times, flashes right headlight three times, then flashes both headlights together three times. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- FM6905: Ford Crown Victoria Police Package, 2006-current. 12V DC Solid state flasher. Three customer selectable flash patterns. High beam override and night time cut off. Handles up to 55 watts per output. Plug-n-Play
Flash Rate: 1.9, 3.0, or variable 1.9-3.9 flashes per second per lamp. (depending on flash pattern selected)
- FM6906: Chevrolet Impala Police Package, 2006-current. 12V DC Solid state flasher. Alternately flashes headlights. High beam override. Handles up to 55 watts per output. Plug-n-Play
Flash Rate: 3.0 flashes per second per lamp.
- H. DRL366-1: Heavy-duty daytime running light module with taillight output, park brake override.



TOLL FREE FAX LINE: 1-888-478-2797 WWW.STARHEADLIGHT.COM

