

# Star Warning Systems®

## 242 Series Strobes with LED Diagnostics



**242C Series**



**242S Series**

### Specs & Features:

- **\*\*Patented\*\*** LED diagnostic indicator (the LED flashes when the strobe tube should flash...if the LED is flashing but the tube is not, it's an indication of a strobe tube failure)
- Photocell for automatic Day/Night mode switching
- Field selectable flash pattern via internal jumper:  
Standard Quad Flash or Selectable Random Flash
- Durable polycarbonate lens
- Long-life flash tube
- Completely encapsulated circuit for increased weather and shock resistance
- Rugged die-cast aluminum base with powder coat finish and universal mounting
- Standard 1/2" pipe mount (Available 1" pipe mount)
- Reverse polarity protected
- Dimensions: 242C Series: 6" H x 5-1/2" Dia.  
242S Series: 4-1/4" H x 5-1/2" Dia.
- Voltage: 10V DC thru 30V DC
- Amp Draw: 2.0 Amps @ 12V DC, 1.0 Amps @ 24V DC
- Joule Rating: 19.5 Joules @ 21 Watts (Quad flash mode)
- Flash Rate: 65 Quad flash sequences per minute
- Approvals: 242CFL: SAE J1318 Class 1; Amber, Blue, Clear  
SAE J1318 Class 2; Red  
242SFL: SAE J1318 Class 1; Blue, Clear  
SAE J1318 Class 2; Amber, Red  
242CFL & 242SFL are AMECA listed
- Lens Color: Amber, Blue, Clear, Red



PROUDLY MADE IN THE U.S.A.  
An ISO 9001:2008 Certified Company

## Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414

Phone: 585-226-9787 FAX: 888-478-2797



www.starheadlight.com

SF007 REV - 9-1-06