

Star Warning Systems®

255T Series Strobes "Star's with a TWIST"



255TC



255TCM



255TCV



255TS



255TSM



255TSV



Specs & Features:

- Field selectable flash pattern via internal jumper:
(Standard Quad Flash or Selectable Double Flash)
- Durable polycarbonate, *Twist-Off* lens
- Features a durable and lightweight polycarbonate plastic, universal flange base
(3-hole permanent mount, 1" pipe mount mount, or magnetic mount with cig plug adapter)
- Completely encapsulated circuit for increased weather and shock resistance
- Automatic low voltage shutdown below 9.5V DC
- Dimensions: 255TS, 255TSM, 255TSV: 4-3/4" tall x 6-13/32" dia.
255TC, 255TCM, 255TCV: 6-11/16" tall x 6-13/32" dia.
- Voltage: 10V DC – 48V DC (permanent mount with wire leads)
10V DC – 16V DC (magnetic mount with cig plug adapter)
- Amp Draw: 1.2A@12V DC, .6A@24V DC, .3A@36V DC, .175A@48V DC
- Joule Rating: 10 Joule Quad Flash – 7 Joule Double Flash
- Flash Rate: 65 QFPM – 80 DFPM
- Approvals: SAE J1318, Class II in Quad Flash Mode:
Amber, Blue, Clear, Red
- Lens Colors: Amber, Blue, Clear, Red



PROUDLY MADE IN THE U.S.A.
An ISO 9001:2008 Certified Company

Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414

Phone: 585-226-9787 FAX: 888-478-2797



www.starheadlight.com

SF021 REV - 02-08-07