

# Star Warning Systems®

LED BEACONS

## 200AH8L & 200AHL Series Star Halo™ LED Beacons

**NEW  
LED  
Technology!**



**Exceeds  
Latest  
J845 and CA13  
Standards**

### Specs & Features:

- 24 Customer selectable flash patterns and 2 rotating patterns
- S-LINK SYSTEM™ synchronizing capability with other STAR LED units
- High/Low Intensity – Manual or Automatic
- Extremely low current draw
- Durable polycarbonate inner lens
- Clear, smooth outer dome for easy cleaning and provides inner lens protection
- Heavy-duty spun aluminum base with anodized finish
- Available as permanent mount or 1" pipe mount
- Completely encapsulated circuit for increased weather and shock resistance
- Dimensions: 7-3/4" tall x 9" dia.
- Voltage: 12V–24V DC
- Amp Draw: 0.6 Amps @ 12V DC, 0.3 Amps @ 24V DC
- LED Colors: Amber, Blue, Red, White
- Lens Colors: Amber, Blue, Clear, Green, Red

**Patent  
Pending!**

**S-LINK  
SYSTEM™**

**YES THE  
U.S.**

### Model Numbers / Descriptions: (classifications for AMBER only)

- 200A1H8L: SAE Class I, California Title 13, Ultra High Intensity LEDs, 1" pipe mount
- 200AH8L: SAE Class I, California Title 13, Ultra High Intensity LEDs, permanent mount
- 200A1HL: SAE Class I, High Intensity LEDs, 1" pipe mount
- 200AHL: SAE Class I, High Intensity LEDs, permanent mount



PROUDLY DESIGNED AND  
ASSEMBLED IN THE U.S.A.  
An ISO 9001:2008 Certified Company

## Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414

Phone: 585-226-9787 FAX: 888-478-2797

**STAR  
WARNING  
SYSTEMS**

**Signal**  
VEHICLE PRODUCTS

**STAR**  
SINCE  
1889

**Signal**  
VIDEO PRODUCTS

**BRADFORD**  
Vehicle Solutions Inc.

www.starheadlight.com

# Star Warning Systems®

## 200BH8L & 200BHL Series Star Halo™ LED Beacons

**NEW  
LED  
Technology!**



**Exceeds  
Latest  
J845 and CA13  
Standards**

### Specs & Features:

- 24 Customer selectable flash patterns and 2 rotating patterns
- S-LINK SYSTEM™ synchronizing capability with other STAR LED units
- High/Low Intensity – Manual or Automatic
- Extremely low current draw
- Durable polycarbonate inner lens
- Clear, smooth outer dome for easy cleaning and provides inner lens protection
- Heavy-duty spun aluminum enclosed base with anodized finish
- Completely encapsulated circuit for increased weather and shock resistance
- Dimensions: 6-7/8" tall x 8-1/4" dia.
- Voltage: 12V–24V DC
- Amp Draw: 0.6 Amps @ 12V DC, 0.3 Amps @ 24V DC
- LED Colors: Amber, Blue, Red, White
- Lens Colors: Amber, Blue, Clear, Green, Red

**Patent  
Pending!**

**S-LINK  
SYSTEM™**

### Model Numbers / Descriptions: (classifications for AMBER only)

200BH8L: SAE Class I, California Title 13, Ultra High Intensity LEDs, permanent mount or 3/4" pipe mount

200B1H8L: SAE Class I, California Title 13, Ultra High Intensity LEDs, permanent mount or 1" pipe mount

200BHL: SAE Class I, High Intensity LEDs, permanent mount or 3/4" pipe mount

200B1HL: SAE Class I, High Intensity LEDs, permanent mount or 1" pipe mount

**YES THE  
U.S.™**



PROUDLY DESIGNED AND  
ASSEMBLED IN THE U.S.A.  
An ISO 9001:2008 Certified Company

## Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414

Phone: 585-226-9787 FAX: 888-478-2797



www.starheadlight.com