## **STAR HALO® BEACON**







## **FEATURES & BENEFITS**

- Star Halo® LED technology is patented (#8,662,702)
- Twelve different selectable flash patterns in either of two phases, plus Steady-On
- S-Link System<sup>™</sup> synchronizing capabilities with other Star LED units
- Extremely low current draw
- Durable polycarbonate lens
- Rugged die-cast aluminium base with powder coat finish
- Permanent mount with ½" pipe mount or optional magnet mount with cig. plug (0n/Off switch and Pattern Select)

- Dimensions: 6 1/4"H x 5 1/2"Dia.
- Voltage: permanent mount 10-30V DC, magnet mount - 10-16V DC
- Amp draw:
  Ultra high intensity 0.7 amps @ 12V DC, 0.4 amps @ 24V DC
  High intensity 0.6 amps @ 12V DC, 0.3 amps @ 24V DC
- Colors for 4-LED version:
- Colors for 8-LED version:
- Approvals: Exceeds SAE Class I J845

PART	DESCRIPTION
200SH8L	Star Halo®, ultra high intensity, permanent mount
200SH8LM	Star Halo®, ultra high intensity, magnet mount, cig. plug
200SHL	Star Halo®, high intensity, permanent mount
200SHLM	Star Halo®, high intensity, magnet mount, cig. plug

⚠ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF110 Rev-D 09-07-2023



