

251 HALO™



Convert “Dish-Style” mount strobe beacons to super-efficient Halo LEDs!



Specs & Features:

- This light is a LED direct replacement for lights that install on a 6 1/2” “Dish” style base
- Lightweight polycarbonate, universal flange base attached to an open aluminum spun base
- J-Hook mount kit included
- 24 customer selectable flash patterns including the rotating pattern (H8 only)
- S-LINK SYSTEM™ synchronizing capability with other STAR LED units
- Selectable High/Low Intensity
- Extremely low current draw
- Completely encapsulated circuit for increased weather and shock resistance
- Dimensions: (Short Dome): 6-7/8” x 6-1/2”
(Tall Dome): 8-21/32” x 6-1/2”
- Voltage: 12-24V DC (permanent mount)
- Amp Draw: 0.7 Amps @ 12V DC, 0.35 Amps @ 24V DC
- Lens Colors: Amber, Blue, Clear, Green, Red
- Low voltage warning
- Approvals: SAE Class 1(Amber)
- Add optional BB274-251K (aluminum spun base kit to mount to an existing 255series light)



(Available without branch guard)

Model Number/ Description:

- 251H8TAL: Ultra High Intensity LEDs and tall dome with dust cover
- 251H8TCL: Ultra High Intensity LEDs and tall dome
- 251H8TSL: Ultra High Intensity LEDs and short dome
- 251H8TAL-BG: Ultra High Intensity LEDs, tall dome with dust cover and branch guard
- 251H8TCL-BG: Ultra High Intensity LEDs, tall dome and branch guard
- 251H8TSL-BG: Ultra High Intensity LEDs, short dome and branch guard
- 251HTAL: High Intensity LEDs and tall dome with dust cover
- 251HTCL: High Intensity LEDs and tall dome
- 251HTSL: High Intensity LEDs and short dome
- 251HTAL-BG: High Intensity LEDs, tall dome with dust cover and branch guard
- 251HTCL-BG: High Intensity LEDs, tall dome and branch guard
- 251HTSL-BG: High Intensity LEDs, short dome and branch guard

