STAR HALO[®] DUAL-COLOR LED BEACON 258HTD*





258HTDL

FEATURES & BENEFITS

- Star Halo[®] technology is patented (#8,662,702)
- Dual-Color Generation IV LEDs (four of each color)
- 12 customer selectable flash patterns including rotating patterns, plus steady-on
- · Individual pattern select for each color
- Ability to change the priority to have one enable override the other
- Ability to flash both colors with one switch
- S-Link System™ synchronizing capability with other Star LED units
- Extremely low current draw
- Fully encapsulated circuit for increased weather and shock resistance
- Lightweight polycarbonate, universal flange base: 3-hole permanent mount, 1" pipe mount

- Also available in vacuum magnet mount
- Cig. plug with dual power on/off switch
- Low voltage warning
- Dimensions: Short dome - 4 ³/₄"H x 6 ¹³/₃₂"Dia. Tall dome - 6 ¹¹/₁₆"H x 6 ¹³/₃₂"Dia.
- Voltage: Permanent mount - 12-24V DC Vacuum magnet mount - 12V DC
- Amp draw: 0.7 amps @ 12V DC, 0.35 amps @ 24V DC
- Lens color:
- LED colors:
- Approvals: short dome SAE Class II (Red/White, Amber/Red, Red/Blue, Amber/Blue)Tall dome: SAE Class I (Amber/Blue, Amber/White) SAE Class II (Amber/Red, Red/White)

PART	DESCRIPTION

258HTDAL	Star Halo®, Dual-Color LEDs, tall dome with dust cover, permanent mount
258HTDALV	Star Halo®, Dual-Color LEDs, tall dome with dust cover, vacuum magnet
258HTDCL	Star Halo®, Dual-Color LEDs, tall dome, permanent mount
258HTDCLV	Star Halo®, Dual-Color LEDs, tall dome, vacuum magnet
258HTDSL	Star Halo®, Dual-Color LEDs, short dome, permanent mount
258HTDSLV	Star Halo®, Dual-Color LEDs, short dome, vacuum magnet

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



FOR MORE INFORMATION VISIT OUR WEBSITE. STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC 455 Rochester St., Avon, NY 14414 Phone: 585-226-9500 | Fax: 888-478-2797

SF132 258HTDL Rev E 7-27-23



STAR HALO[®] DUAL-COLOR LED BEACON 258HTD*





FEATURES & BENEFITS

- Star Halo[®] technology is patented (#8,662,702)
- Dual-Color Generation IV LEDs (four of each color)
- Halo rotating, two color LEDs
- 12 customer selectable flash patterns including rotating patterns, plus steady-on
- Individual pattern select for each color
- Ability to change the priority to have one enable override the other
- · Ability to flash both colors with one switch
- S-Link System[™] synchronizing capability with other Star LED units
- Extremely low current draw
- Fully encapsulated circuit for increased weather and shock resistance

- Rugged die-cast aluminum base
- Low voltage warning
- Permanent mount, standard ½" pipe mount, optional magnet mount with cig. plug (on/off and pattern selection switch)
- Dimensions: Short dome - 4 ³/₄"H x 6 ¹³/₃₂"Dia. Tall dome - 6 ¹¹/₁₆"H x 6 ¹³/₃₂"Dia.
- Voltage: Permanent mount - 12-24V DC, Vacuum magnet mount - 12V DC
- Amp draw: 0.7 amps @ 12V DC, 0.35 amps @ 24V DC
- Outer dome color:
- LED colors:
- Approvals: SAE Class II (Amber/Blue)

PART DESCRIPTION

200SHDL	Star Halo®, Dual-Color LEDs, permanent mount
200SHDLM	Star Halo®, Dual-Color LEDs, magnet mount

Marning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



FOR MORE INFORMATION VISIT OUR WEBSITE. STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC 455 Rochester St., Avon, NY 14414 Phone: 585-226-9500 | Fax: 888-478-2797



SF132 258HTDL Rev E 7-27-23