



MODEL	DESCRIPTION	CERT MARKING
DLXTHR-2-GC	4" ROUND; GREEN; 9-32VDC; FOUR WIRE; 3 PIN CONNECTOR; S-LINK+; 36 LED'S.	N/A
DLXTHR-8-A	4" ROUND; AMBER; 9-32VDC; GROMMET MOUNT; FOUR WIRE; 3 PIN CONNECTOR; S-LINK+; 36 LED'S.	SAE W-1 14
DLXTHR-8-BC	4" ROUND; BLUE; 9-32VDC; GROMMET MOUNT; FOUR WIRE; 3 PIN CONNECTOR; S-LINK+; 36 LED'S.	SAE W-1 14

REV.	ECR	DESCRIPTION	DATE
-	17518	INITIAL DRAWING REQUEST	09/23/2020
A	17750	ADDED CERT MARKINGS	1/12/2021

SPECIFICATIONS:

OPERATING RANGE: 10-16VDC / 19-30 VDC
 NOMINAL VOLTAGE: 12/24 VDC
 TYPICAL CURRENT DRAW: 12.8VDC=0.3A AVERAGE 0.6A PEAK
 OPERATING TEMPERATURE RANGE: -40F (-40C) TO 131F (55C)

CONNECTIONS: TYCO P/N 282105-1

PIN 1 22 GAGE BLACK WIRE 8.0"(203mm) LONG - GROUND
PIN 2 22 GAGE WHITE WIRE 8.0"(203mm) LONG SYNCHRONIZATION
PIN 3 22 GAGE RED WIRE 8.0"(203mm) + POWER
 22 GAGE GREEN WIRE 8.0"(203mm) LONG - PATTERN SELECT

INSTALLATION:

*NO MOUNT PROVIDED (REPLACEMENT HEAD ONLY)-2
 *GROMMET MOUNT -8

MATERIALS:

MODULE LENS: POLYCARBONATE
 MODULE HOUSING: POLYCARBONATE

CERTIFICATIONS:

SAE J595 CLASS I
 SEE CHART

PRODUCT LABEL:

WHITE POLYESTER STOCK 3" X .375"
 BLACK PRINT STAR LOGO

INDIVIDUAL PACKAGING: APPROXIMATELY [.34Kg](0.75 lb.)

COLOR HEADER CARD
 POLY BAG

INSTRUCTION SHEET:

1 PROVIDED ENGLISH

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES

TOLERANCES:

ANGULAR: ± 2 DEG.

.X ± .100

.XX ± .020

.XXX ± .005

.XXXX ± .001

RoHS COMPLIANT: Yes

MATERIAL:

N/A

FINISH:

N/A

DRAWN BY: MD

DRAWING APPROVED BY ECR

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAR HEADLIGHT & LANTERN CO., INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC. IS STRICTLY PROHIBITED.

STAR HEADLIGHT & LANTERN CO., INC.

455 Rochester St. Avon NY 14414
 Ph:(585) 226-9500 Fax: (585) 226-2029

MODEL: DLXTHR-*-*

TITLE: MODEL DRAWING

DWG. NO.

DLXTHR-2 REV 001

REV

A

SCALE: 1:2

DO NOT SCALE FROM DRAWING

SHEET 1 OF 1