200S WARNING BEACON







FEATURES & BENEFITS

- Star X-Fire[®] technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Exceeds SAE Class I J845 standards
- S-Link System[™] synchronizing capabilities with other Star LED units, hardwire only
- Extremely low current draw
- Durable polycarbonate lens
- Rugged die-cast aluminum base with powder coated finish
- Universal permanent mount, standard ½" pipe mount, optional magnet mount with cig. plug (on/off switch and pattern select)

- Dimensions: 4 ¼"H x 5 ½"Dia.
- Voltage: permanent mount 9-32V DC, magnet mount 9-16V DC
- Amp draw: 0.6 amps @ 12V DC, 0.3 amps @ 24V DC
- Lens colors: 🔤 📑 📕 📃
- LED colors with clear dome:
- Approvals: SAE Class I (available not all colors)

PART	DESCRIPTION
200S-12V-*	Warning Beacon; Amber; 9-32 VDC
200SM-12V-*	Warning Beacon; Amber; 9-16 VDC, Magnet mount

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



FOR MORE INFORMATION VISIT OUR WEBSITE. STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC 455 Rochester St., Avon, NY 14414 Phone: 585-226-9500 | Fax: 888-478-2797



Safety Technologies by Grote