

MODELS	DESCRIPTIONS	CERT. MARKING	
64-102	back up alarm; single tone @ 102 db	SAEJ994 TYPE F	





REV.	ECR	DESCRIPTION	DATE
-	16685	INITIAL DRAWING REQUEST	07/10/19
Α	16804	ADDED 16-18 AWG TO BUTT SPLICE DESCRIPTION	9/23/2019

## **BACK UP ALARM SPECIFICATIONS OPERATING RANGE: 9-32 VDC** NOMINAL VOLTAGE: 12/24 VDC TYPICAL CURRENT DRAW: 0.3 AVG. @ 14VDC TYPICAL POWER: 4.2W @ 14VDC OPERATING TEMPERATURE: -40C° (-40°F) TO +85C°(+185°F) CONNECTIONS: 18 GAGE RED WIRE 12" LONG WITH 16-18 AWG BUTT SPLICE /A 18 GAGE BLACK WIRE 3" LONG WITH 1/4" RING TERMINAL PERFORMANCE: SINGLE TONE @102 ±4 dB MATERIALS: 10-15% GLASS FILLED NYLON BLACK URETHANE POTTING MATERIAL: TO BE SUBSTANTIALLY FLUSH AND LEVEL WITH BACK OF HOUSING CERTIFICATIONS: SAE J994 SEPTEMBER-2014 PRODUCT LABEL: POLYESTER STOCK ~20mm X 50mm BLACK BACK GROUND WHITE PRINT CENTERED ON TOP OF ALARM DATE CODE: ALARM TO BE LEGIBLY MARKED WITH DATE CODE WEEK; YEAR EX. 5017 ORIGIN: MARKED ON BACK OF ALARM "MADE IN TAIWAN" INDIVIDUAL PACKAGING: APPROXIMATELY 300g(10.5oz) INDIVIDUAL COLOR PRINT BOXES MODEL INFORMATION PRINTED ON BOX OR ON LABEL LOCATED ON 3 SIDES OF BOX (ARTWORK TO BE SUPPLIED) MODEL BAR CODE ON BOX TAPE OR LABEL TO HOLD BOX FLAP CLOSED BULK PACKAGING: APPROXIMATELY 15Kg (33.1lbs.) 50 PER MASTER CARTON DASHBOARD WARNING LABELS: 3.188 X 2.25 WHITE SYNTHETIC VINYL BLACK LETTERING AND SAFETY ORANGE 3 PROVIDED (ENGLISH, SPANISH)

## INSTRUCTION SHEET:

1 PROVIDED (ENGLISH, SPANISH)

UNLESS OTHERWISE SPE DIMENSIONS ARE IN IN		STAR HEADLIGHT & LANTERN CO., INC
TOLERANCES: ANGULAR: ± 2 DEG	THE INFORMATION CONTAINED I DRAWING IS THE SOLE PROPERTY	Ph:(585) 776-9500 Fax: (585) 776-7079
.X ± .100 .XX ± .020 .XXX ± .005	STAR HEADLIGHT & LANTERN CO ANY REPRODUCTION IN PART OF WHOLE WITHOUT THE WRITTEN PE	AS A MODEL: 64-102 REV:001
.XXXX ± .001 Rohs COMPLIANT: YES	OF STAR HEADLIGHT & LANTERN IS STRICTLY PROHIBITED.	
MATERIAL: N/A		DWG. NO. REV 64-102 A
FINISH: N/A		SCALE: 1:2 DO NOT SCALE FROM DRAWING SHEET 1 OF 1